

## THD2FE – NON-CONTACT FOREHEAD THERMOMETER



Forehead mode: 93.2 to 108°F/34 to 42.2°C;  
Surface mode: -7.6 to +176°F/-22 to +80°C

0 18436 00577 3

- For measurement of human body temperature in people of all ages
- Response Time: Forehead mode: 1 second; Surface mode: 0.6 second
- Forehead Measurement Distance: within 1.5 in/4 cm
- Surface mode: Distance:Spot = 1:1, emissivity: 0.95
- Accuracy: Forehead mode:  $\pm 0.4^\circ\text{F}/0.2^\circ\text{C}$ ; Surface mode:  $\pm 0.5^\circ\text{F}/0.3^\circ\text{C}$
- Backlit in blue
- Memory recalls 25 readings
- One-button operation
- Battery status indication
- Water Resistant (IP22)
- Temperature alert or silent
- On/Off Power button
- Auto-off after 1 minute
- ABS plastic
- Two 1.5V AAA IEC LR03 alkaline batteries (included)
- FDA, RoHS, ISO 9001, ISO 13485, ASTM E1965-98, EN ISO 80601-2-56

List price: **140.00**

Now shipping

## TCTW572 – WATERPROOF FOLDING THERMOCOUPLE THERMOMETER



-58 to +572°F/-50 to +300°C

0 18436 00508 7

- NSF<sup>®</sup> Certified
- 4-way rotating display
- 3-second response
- 1.5 mm thin tip
- 4.33"/11.0 cm probe
- Waterproof (IPX7: protected from water up to 3 feet/1 meter for 30 minutes)
- Extra big digit
- Backlit display
- Field calibration
- Automatic on/off
- Food-safe ABS plastic with BioCote<sup>®</sup>
- 304 stainless steel probe
- Temperature guide on thermometer
- Mounting: loop
- Two AAA 1.5V IEC LR03 alkaline batteries (included)

List price: **76.00**

Now shipping



## DTTW572 – WATERPROOF THIN TIP THERMOMETER



-40 to +572°F/-40 to 300°C

0 18436 00507 0

- NSF<sup>®</sup> Certified
- 4-second response
- 1.5 mm thin tip
- 3.5"/8.9 cm stem
- Waterproof (IPX7: protected from water up to 3 feet/1 meter for 30 minutes)
- Field calibration
- High heat
- Max/min
- Data-hold
- Big digit
- 180° rotating display
- On/off button
- Auto-off after 10 minutes
- Food-safe ABS plastic with BioCote<sup>®</sup>
- 304 stainless steel stem
- Temperature guide on thermometer
- 2-way mounting: pocket clip/hook
- Two 1.5V IEC LR44 button alkaline batteries (included)

List price: **32.00**

Available 10-20



## IN482 – INFRARED THERMOMETER, TIMER & CLOCK



-67 to 482°F/-55 to +250°C

0 18436 00573 5

- For non-contact surface temperatures
- One-button operation
- 1-second response
- Distance:Spot = 5:1
- Stopwatch timer
- Clock
- Ambient temperature
- Shatterproof
- Maximum, minimum and lock for continuous scanning
- $\pm 3.6^\circ\text{F}/2^\circ\text{C}$  accuracy
- Battery status indication
- Food-safe ABS plastic
- Auto-off after 15 seconds
- 2-way mounting: stand/loop
- One 3V IEC CR2032 lithium button battery (included)

List price: **47.35**

Now shipping



## AW200 – ALCOHOL PADS - PACKETS



200 Single Use Packets

0 18436 00934 4

- FDA-listed, EPA & NQA certified
- For cleaning thermometer stems and probes
- Each wipe saturated with 75% Isopropyl Alcohol
- Pad Size: 1.18 x 2.36 (in)/3 x 6 (cm)
- Expiration date on package in lieu of warranty

Limited Time Offer

List price: **9.75**

**Now shipping**

## PW1000 – ALCOHOL WIPES - 5X200 PACKETS



5 Boxes of 200 Single Use Packets

0 18436 00919 1

- FDA-listed, EPA & NQA certified
- For cleaning thermometer stems and probes
- Each wipe saturated with 75% Isopropyl Alcohol
- Pad Size: 1.2 x 2.2 (in)/3 x 5.5 (cm)
- Expiration date on package in lieu of warranty

75% Isopropyl Alcohol

List price: **45.00**

**Now shipping**

## DW2 – DISHWASHER THERMOMETER



32 to 194°F/0 to 90°C

0 18436 00498 1

- NSF® Certified
- LED indication lights for different maximum temperatures
- Waterproof IP66
- Max/min
- Last maximum temperature recall
- Extra big digit
- Triple display
- On/off button
- Two 3V IEC CR2032 lithium batteries (included)
- Storage case (included)

List price: **64.00**

**Now shipping**

## SD2206 – DIGITAL PORTION CONTROL SCALE, 22 LB



22 lb/352 oz/10 kg by lb:oz/oz/g

0 18436 00834 7

- Tare function
- Backlit display
- Field calibration
- Zero setting function
- Piece counting
- Selectable units
- Overload indication
- Battery status indication
- ABS plastic housing
- Removable stainless steel platform
- On/off button
- Auto-off after 11 minutes
- Platform Size: 5.9 W x 5.9 L (in)/ 15.0 W x 15.0 L (cm), removable
- Resolution: 0 lb:0.1 oz, 0.1 oz, 2 g
- Two 1.5V AAA batteries, included
- Power Adapter: 100-120 VAC 50/60 Hz input, 9 V DC (500 mA) output, included

List price: **49.00**

**Now shipping**

